



High quality stainless steel coils

We produce a wide variety of stainless steel coils in different standard and customized dimensions. They are a broad range of applications in any industry. The products are produced under environmental supervision and all our products are manufactured with first quality raw material. All our products have an excellent corrosion and heat resistance. The average stock effective is more than 1'000 metric tons of stainless steel materials, becoming the largest on-hand stainless steel products platform with complete range for all our customers.

Stainless steel coils



Grade	Thickness	Surface
304/304H	0.25 - 12 mm	2B, BA, No. 4, 8K, SB, HL, No. 1
304L	0.50 - 12 mm	2B, BA, No. 4, 8K, SB, HL, No. 1
304/304L	0.50 - 12 mm	2B, BA, No. 4, 8K, SB, HL, No. 1
321	0.50 - 12 mm	2B, BA, No. 4, 8K, SB, HL, No. 1
316/316L/316Ti	0.50 - 12 mm	2B, BA, No. 4, 8K, SB, HL, No. 1
317Ti	0.50 - 12 mm	2B, No. 4, No. 1
409L	0.40 - 2.5 mm	2B, 2D
430	0.40 - 3.0 mm	2B, BA, No. 4, 8K, SB, HL
443	0.40 - 2.0 mm	2B, KB
436L/439/444/441	0.50 - 3.0 mm	2B
304J1	0.40 - 3.0 mm	2B, BA, No. 4, 8K, SB, HL

Standard sizes: on customers request; max. width 2500 mm, max. length 15000 mm

Inside core: 508 mm, 610 mm

Condition: cold rolled, hot rolled, annealed and pickled, polished K180 - K800 upon request

Tolerances: According EN ISO 9445-1, EN ISO 9445-2

Specifications: According ASTM A240, ASTM A480, EN 10088-2, EN 10259, AD 2000 W0

Warranty: Mill test certificate according EN 10204-2.2 and EN 10204-3.1

Quality and Logistics

All our products are manufactured according the EU guidelines and correspond according the EN10204-2.2, EN10204-3.1 directives including the CE compliance. We provide a full service to all our customers as DDP shipments directly to their domicile; without any troubles for the transportation, the ordering of containers, customs, port handling fees and so on for our customers.

